

ICI | 9320 S-Series



Patent No. 9880552

www.infraredcamerasinc.com | sales@infraredcamerasinc.com

INFRARED CAMERAS INC.
2105 W. Cardinal Dr.
Beaumont, TX 77705

Phone: (409) 861-0788
Toll Free: (866) 861-0788

We are IR™

ICI | 9320 S-Series

The ICI 9320 S-Series infrared camera offers unmatched image sensitivity and accuracy in a 320x240 radiometric imager. With less than 2 in³ in overall dimension the 9320 fits in the tightest of areas. The ICI 9320 S operates on less than 1 W of power, via a USB 2.0 connection, providing real time radiometric data streamed directly to any desktop, laptop, tablet or embedded system. Windows and Linux software, drivers and SDK are available for any and all custom applications. Integrates into the Sensor Control Module for UAV applications.



Features

- Unmatched Image Sensitivity
- UAV Connectivity
- Multi-Device Linking
- Radiometric Data Streaming
- Integrates into Embedded Systems
- Small Size < 2"
- Light Weight
- Low Power < 1 W by USB
- Drivers and SDK Available
- Includes IR Flash Software

Applications

- Process Control
- Robotics
- Industrial Vision Systems
- Medical Radiometric Imaging
- Aerial Radiometric Imaging
- UAV Integration
- Scientific Research
- Building Automation
- Security Monitoring



Specifications

- **Detector Array:** UFPA (VOx)
- **Pixel Pitch:** 17 μ m
- **Pixel Resolution:** 320x240
- **Spectral Band:** 7 μ m to 14 μ m
- **Thermal Sensitivity (NETD):** < 0.02 $^{\circ}$ C at 30 $^{\circ}$ C (20 mK)
- **Frame Rate:** 60 Hz P-Series
- **Dynamic Range:** 14-bit
- **Temperature Range:** -40 $^{\circ}$ C to 140 $^{\circ}$ C
- **Operation Range:** -40 $^{\circ}$ C to 80 $^{\circ}$ C
- **Storage Range:** -40 $^{\circ}$ C to 70 $^{\circ}$ C
- **Accuracy:** \pm 1 $^{\circ}$ C
- **Pixel Operability:** > 99 %
- 75 G Shock / 4 G Vibration
- **Dimensions (without lens):** 34 x 30 x 34 mm (H x W x D \pm .5 mm)
- **Power:** < 1 W
- **Weight (without lens):** 37 g
- USB 2.0 for Power & Data
- Built in Shutter
- Aluminum Enclosure

Options & Accessories

- 7.5 mm Manual Focus Lens (40 $^{\circ}$ x 30 $^{\circ}$ FOV, +6 g)
- 7.5 mm Athermalized Lens (40 $^{\circ}$ x 30 $^{\circ}$ FOV, +16 g)
- 11 mm Manual Focus Lens (27 $^{\circ}$ x 20 $^{\circ}$ FOV, +20 g)
- 21 mm Manual Focus Lens (15 $^{\circ}$ x 11 $^{\circ}$ FOV, +22 g)
- 19 mm Athermalized Lens (16 $^{\circ}$ x 12 $^{\circ}$ FOV, +36 g)
- 35 mm Manual Focus Lens (9 $^{\circ}$ x 6.7 $^{\circ}$ FOV, +35 g)
- 35 mm Athermalized Lens (9 $^{\circ}$ x 6.7 $^{\circ}$ FOV, +105 g)
- 1/4-20 Bulkhead Mount
- Sensor Control Module

